

HEATSENSE®

C A B L E S

Specialist High-Performance Solutions

SPECIFICATION DATA SHEET

CABLE TYPE

FEP INSULATED AWM EQUIPMENT WIRE

GENERAL DESCRIPTION

TIN PLATED COPPER CONDUCTORS,
FEP EXTRUDED INSULATION 0.53mm NOMINAL R/T.

RELEVANT STANDARDS

UL STYLE 1331

Heatsense Reference:	Conductor Details				Insulation Thickness (mm)		Overall Diameter		Conductor Resistance (Ω /km @ 20°C)	Mass	Long term current rating*
	Part Number	Size AWG	Stranding (mm)	O/D (mm)	Area (mm ²)	Min. Ave.	Min. AAP	Min. (mm)	Nom. (mm)	SPCW (Max)	Nom. (kg/km)
HSF30TB4.	30	07/0.102	0.30	0.055	0.51	0.46	1.32	1.36	353.00	3.56	2.0
HSF28TB4.	28	07/0.127	0.38	0.089	0.51	0.46	1.40	1.44	223.00	4.01	3.0
HSF26TB4.	26	07/0.160	0.48	0.141	0.51	0.46	1.50	1.54	140.00	4.76	4.0
HSF24TB4.	24	07/0.203	0.60	0.220	0.51	0.46	1.62	1.66	87.60	6.22	6.0
HSF22TB4.	22	07/0.254	0.75	0.343	0.51	0.46	1.77	1.81	52.10	7.94	8.0
HSF22TC4.	22	19/0.160	0.80	0.336	0.51	0.46	1.82	1.86	55.40	7.80	8.0
HSF20TC4.	20	19/0.203	1.00	0.597	0.51	0.46	2.02	2.06	34.60	11.14	11.0
HSF18TC4.	18	19/0.254	1.25	0.933	0.51	0.46	2.27	2.31	21.80	15.17	15.0
HSF16TC4.	16	19/0.300	1.50	1.342	0.51	0.46	2.52	2.56	14.89	19.61	18.0
HSF15TC4.	14/15	19/0.361	1.81	1.946	0.51	0.46	2.83	2.87	9.15	26.60	25.0
HSF13TC4.	12/13	19/0.454	2.25	3.020	0.51	0.46	3.27	3.31	5.75	38.20	35.0
HSF11TD4.	10/11	37/0.404	2.80	4.650	0.51	0.46	3.82	3.86	3.55	54.90	47.0
HSF10TN4.	10	84/0.300	3.00	6.00	0.51	0.46	4.02	4.06	3.23	66.77	55.0

*Current ratings are based on a temperature rise of 40°C (single wire in free air).

Available in 11 basic colours Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, Pink plus natural.
Available in alternative conductor sizes – check for availability.

CABLE CHARACTERISTICS

VOLTAGE RATING: 600 V rms

TEMPERATURE RATING: +150°C

Use

Internal Wiring of Appliances and electronic equipment.
2500 Volts peak – For Electronic Use Only.
Suitable for immersion in gasoline; gasoline vapour; and 80 deg. C in oil.

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of products, no warranty is given nor is implied with respect to such information. Users should make their own enquiries to determine the suitability of products for any particular use. Freedom under patents, copyright and registered designs cannot be assumed.

This design may be subject to change without notification - please check this data sheet is still current.